

Technical Information Sheet

QuickSeam™ Corner Flashing

Packaging	Part Number
20 pieces per carton	W56RAC1646

Description

The Elevate™ QuickSeam Corner Flashing is a 216 mm in diameter round piece of uncured EPDM FormFlash factory-laminated to QuickSeam Tape, adaptable to irregular shapes. It is designed to flash system details (inside and outside corners, reinforcement patches,...) as specified in the Elevate guidelines.

Application

QuickSeam Corner Flashing can be applied in following Elevate system(s): RubberCover™ EPDM, GeoGard™ EPDM and PondGard™ EPDM.

Preparation

The Elevate EPDM surfaces and/or mating surfaces must be prepared with QuickPrime™ primer, using a QuickScrubber™ tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

Method of Application

On cloudy days with ambient temperature below 15°C, the use of a heat gun is recommended to warm the QuickSeam Corner Flashing and to ensure good formability. Refer to the Elevate technical guidelines for specific installation instructions.

Note: QuickSeam Corner Flashing is a non-vulcanized product and mainly cures after installation. Correct use, accurate installation technique and installation according general application practice will result the final characteristics and proper functioning of the product.

Coverage

Piece(s), as per detail requirement.

Characteristics

Technical		
	EPDM Flashing	QuickSeam Tape
• Base	EPDM	Rubber polymers
• Color	Black	Black
• Solvents	None	None
• Solids	100%	100%
• State	Uncured	Cured
• Thickness	1.6 mm	0.6 mm
• Diameter	216 mm	216 mm

Storage

Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Shelf Life

12 months, when stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

Precautions

Refer to Safety Data Sheet.

Note:

This document is meant only to highlight Elevate products and specifications based on latest knowledge and experience and is subject to change without notice. Above mentioned values are based on tested samples and may vary within applicable tolerances. For latest and complete product and detail information, please refer to the technical information posted on www.holcimelevate.com. Holcim Solutions and Products EMEA BV ("Holcim") takes responsibility for furnishing quality materials which meet Holcim's published product specifications. As neither Holcim itself nor its representatives practice architecture, Holcim offers no opinion on and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. The selection of the appropriate product and its correct application is the responsibility of the customer and not of Holcim. No Holcim Representative is authorized to vary this disclaimer.