

Technical Information Sheet



QuickSeam™ SA Flashing

Packaging	Part Number
457 mm x 15.25 m per roll, 1 roll per carton	W56RAC1620

Description

The Elevate™ QuickSeam SA Flashing is a 457 mm (18") wide, 1.5 mm thick non-reinforced EPDM membrane, fully laminated to a QuickSeam Tape. It has a polyester release liner for easy removal and excellent weather resistance. The SA Flashing can be used to easily flash details where cured EPDM is required or preferred. It can also be used for repairing the Elevate EPDM membrane (e.g. cuts and punctures).

Application

QuickSeam SA Flashing can be applied in following Elevate system(s): RubberGard™ EPDM, RubberCover™ EPDM, GeoGard™ EPDM and PondGard™ EPDM.

Preparation

The EPDM surfaces and/or mating surfaces must be prepared with QuickPrime™ primer, using a QuickScrubber™ tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods. When repairing an Elevate EPDM membrane that has been in service for some time, it is necessary to properly clean the membrane before applying the QuickPrime primer. The cleaned area must be larger than the repair area.

Method of Application

Apply the strip in one or two dimensions (flat or maximum one angle change). Install a QuickSeam FormFlash cover patch at overlaps and angle-changes. Refer to the Elevate technical guidelines for specific installation instructions.

Coverage

In accordance with length of detail to be covered. Adjoining strips require a minimum overlap.

Characteristics

Technical	EPDM Membrane	QuickSeam Tape
• Base	EPDM	Rubber polymers
• Color	Black	Black
• Solvents	None	None
• Solids	100%	100%
• State	Cured	Cured
• Thickness	1.5 mm	0.5 mm
• Width	457 mm	460 mm

Storage

Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Shelf Life

24 months can be expected if stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

Precautions

Refer to Safety Data Sheet.

Note:

This document is meant only to highlight Elevate products and specifications based on latest knowledge and experience and is subject to change without notice. Above mentioned values are based on tested samples and may vary within applicable tolerances. For latest and complete product and detail information, please refer to the technical information posted on www.holcimelevate.com. Holcim Solutions and Products EMEA BV ("Holcim") takes responsibility for furnishing quality materials which meet Holcim's published product specifications. As neither Holcim itself nor its representatives practice architecture, Holcim offers no opinion on and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. The selection of the appropriate product and its correct application is the responsibility of the customer and not of Holcim. No Holcim Representative is authorized to vary this disclaimer.