뉡 ELEVATE

SAFETY DATA SHEET

Based upon Regulation (EC) No 1907/2006, as amended by Regulation (EU) No 2020/878

Cleaner C-20

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

| Product name | : Cleaner C-20 |
|---------------------------|----------------------------|
| Registration number REACH | : Not applicable (mixture) |
| Product type REACH | : Mixture |

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant identified uses

Paint remover Professional use Construction

1.2.2 Uses advised against

General population

Other non-specified uses are excluded

1.3. Details of the supplier of the safety data sheet

Supplier of the safety data sheet

Holcim Solutions and Products EMEA Ikaroslaan 75 B-1930 Zaventem Compliance-emea-hbe@holcim.com

1.4. Emergency telephone number

24h/24h : +32 14 58 45 45 (BIG)

```
24h/24h
```

lreland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2166 (Pucblic 8 am- 10 pm) lreland - Beaumont Hospital, Dublin (NPIC): +353 1 809 2566 (Professionals)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

| Class | Category | Hazard statements |
|-----------------|--|---|
| Aerosol | category 1 | H222: Extremely flammable aerosol. |
| Aerosol | category 1 | H229: Pressurised container: May burst if heated. |
| Skin Irrit. | category 2 | H315: Causes skin irritation. |
| Eye Irrit. | category 2 | H319: Causes serious eye irritation. |
| STOT SE | category 3 | H336: May cause drowsiness or dizziness. |
| Aquatic Chronic | quatic Chronic category 2 H411: Toxic to aquatic life with long lasting effects. | |

2.2. Label elements



Contains: hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane; propan-2-ol. Signal word Danger H-statements

Extremely flammable aerosol. H222 Pressurised container: May burst if heated. H229 Causes skin irritation. H315 H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects. H411 P-statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210 Do not spray on an open flame or other ignition source. P211 Do not pierce or burn, even after use. P251

P280 Wear protective gloves, protective clothing and eye protection/face protection.

Created by: Brandweerinformatiecentrum voor gevaarlijke stoffen vzw (BIG) Technische Schoolstraat 43 A, B-2440 Geel http://www.big.be © BIG vzw

Publication date: 2023-06-29

18352-037-en

878-

P304 + P340 P410 + P412 **Cleaner C-20**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F.

2.3. Other hazards

May build up electrostatic charges: risk of ignition Gas/vapour spreads at floor level: ignition hazard Caution! Substance is absorbed through the skin

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | CAS No EC No List No | Conc. (C) | Classification according to CLP | Note | Remark | M-factors and ATE |
|---|----------------------------|-----------|--|------------|-------------|----------------------|
| hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane 01-2119475514-35 | | ≤C≤90% | Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Chronic 2; H411 | (1)(2)(10) | Constituent | |
| propan-2-ol | | ≤C≤30% | Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 | (1)(2)(10) | Constituent | |

(1) For H- and EUH-statements in full: see section 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

Note: numbers 9xx-xxx-x are provisional list numbers assigned by Echa pending an official EC inventory number

SECTION 4: First aid measures

4.1. Description of first aid measures

General:

Observe (own) safety. If possible, approach victim and check vital functions. In case of injury and/or intoxication, call the European emergency number 112. Treat symptoms starting with most life-threatening injuries and disorders. Keep victim under observation, possibility of delayed symptoms.

After inhalation:

Remove victim into fresh air. In case of respiratory problems, consult a doctor/medical service.

After skin contact:

If possible, wipe up/dry remove chemical. Then rinse/shower immediately with (lukewarm) water. If irritation persists, consult a doctor/medical service.

After eye contact:

Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, consult a doctor/medical service.

After ingestion:

Rinse mouth with water. If you feel unwell, consult a doctor/medical service. Do not wait for symptoms to occur to consult Poison Center.

4.2. Most important symptoms and effects, both acute and delayed

4.2.1 Acute symptoms

After inhalation: Dizziness. Drowsiness. Headache. Nausea. Impaired concentration. Feeling of weakness. After skin contact: Tingling/irritation of the skin. After eye contact: Irritation of the eye tissue. After ingestion: No effects known.

4.2.2 Delayed symptoms No effects known.

4.3. Indication of any immediate medical attention and special treatment needed

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1. Extinguishing media

5.1.1 Suitable extinguishing media:

Small fire: Water, Quick-acting ABC powder extinguisher, Quick-acting BC powder extinguisher, Quick-acting CO2 extinguisher. Major fire: Quantities of water.

5.2. Special hazards arising from the substance or mixture

Upon combustion: CO and CO2 are formed. Pressurised container: May burst if heated.

5.3. Advice for firefighters

5.3.1 Instructions:

Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. If exposed to fire cool the closed containers by spraying with water. After cooling: persistant risk of physical explosion. Take account of environmentally hazardous firefighting water.

5.3.2 Special protective equipment for fire-fighters:

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Heat/fire exposure: selfcontained breathing apparatus (EN 136 + EN 137).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See section 8.2

6.1.2 Protective equipment for emergency responders

Gloves (EN 374). Protective goggles (EN 166). Head/neck protection. Protective clothing (EN 14605 or EN 13034). Suitable protective clothing

See section 8.2

6.2. Environmental precautions

Contain released product. Dam up the liquid spill.

6.3. Methods and material for containment and cleaning up

Take up liquid spill into a non combustible material e.g.: sand/kieselguhr. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See section 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1. Precautions for safe handling

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Avoid prolonged and repeated contact with skin.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Meet the legal requirements. Keep container in a well-ventilated place. Fireproof storeroom. Keep out of direct sunlight.

7.2.2 Keep away from:

Heat sources, ignition sources.

- 7.2.3 Suitable packaging material:
 - Aerosol

7.2.4 Non suitable packaging material:

No data available

7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 Occupational exposure

a) Occupational exposure limit values If limit values are applicable and available these will be listed below.

| Alcool isopropylique | Time-weighted average exposure limit 8 h | 200 ppm |
|----------------------|--|------------------------|
| | Time-weighted average exposure limit 8 h | 500 mg/m ³ |
| | Short time value | 400 ppm |
| | Short time value | 1000 mg/m ³ |
| rance | | |
| Alcool isopropylique | Short time value (VL: Valeur non réglementaire indicative) | 400 ppm |

| Alcool isopropylique | | | Sho | rt time value (VL: Val | eur non réglement | taire indicative) | 980 mg/m ³ |
|--|--|---|--|---|---|------------------------|-----------------------------------|
| lydrocarbures en C6-C12 (en | semble des, | vapeurs) | Tim | e-weighted average | exposure limit 8 h | | 1000 mg/m ³ |
| | | | _ | ementaire indicative rt time value (VL: Val | | taire indicative) | 1500 mg/m ³ |
| Germany | | | 10.10 | | | | |
| Kohlenwasserstoffgemische, ' | Verwendung | als Lösemittel | I Time | e-weighted average exp | oosure limit 8 h (TRG | S 900) | |
| Lösemittelkohlen wasserstoff Aliphaten | fe), additiv-fr | ei: C6-C8 | | | · | · | |
| Propan-2-ol | | | | e-weighted average exp | | | 200 ppm |
| | | | Time | e-weighted average exp | posure limit 8 h (TRG | S 900) | 500 mg/m ³ |
| Austria | | | | | | | |
| -Propanol Kurzzeitwert für G | iroßguss | | | esmittelwert (MAK) | | | 200 ppm |
| | | | | esmittelwert (MAK) | | | 500 mg/m ³ |
| | | | | zeitwert 30(Miw) 4x (N | | | 800 ppm 2000 mg/m ³ |
| -Propanol | | | _ | zeitwert 30(Miw) 4x (N esmittelwert (MAK) | ЛАК) | | 2000 mg/m 200 ppm |
| | | | | esmittelwert (MAK) | | | 500 mg/m ³ |
| | | | | zeitwert 15(Miw) 4x (N | ЛАК) | | 800 ppm |
| | | | Kurz | zeitwert 15(Miw) 4x (N | ЛАК) | | 2000 mg/m ³ |
| ЈК | | | _ | | | | |
| Propan-2-ol | | | (EH4 | e-weighted average exp 40/2005)) | | | 400 ppm |
| | | | | e-weighted average exp 40/2005)) | oosure limit 8 h (Wor | rkplace exposure limit | 999 mg/m³ |
| | | | _ | rt time value (Workplac | ce exposure limit (EH | 40/2005)) | 500 ppm |
| | | | Shor | rt time value (Workplac | ce exposure limit (EH | 40/2005)) | 1250 mg/m ³ |
| JSA (TLV-ACGIH) | | | | | | | |
| | | | | | | | |
| 2-propanol | | | Time | e-weighted average exp | oosure limit 8 h (TLV | - Adopted Value) | 200 ppm |
| 2-propanol | PS | | | e-weighted average exp rt time value (TLV - Ado | | - Adopted Value) | 200 ppm 400 ppm |
| 2-propanol b) National biological limit value f limit values are applicable and Germany | available the | | Shor below. | rt time value (TLV - Ado | opted Value) | - Adopted Value) | |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) | available thes | n: expositionsend | Shor pelow. de, bzv | rt time value (TLV - Add w. schichtende | 25 mg/l | - Adopted Value) | |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) | available thes | n: expositionsend | Shor pelow. de, bzv | rt time value (TLV - Ado | opted Value) | - Adopted Value) | |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) | available thes | n: expositionsend | Shor pelow. de, bzv sende, | rt time value (TLV - Add w. schichtende , bzw. schichtende | 25 mg/l 25 mg/l | | 400 ppm |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) | available thes | n: expositionsend blut: expositions | Shor pelow. de, bzv sende, | rt time value (TLV - Add w. schichtende , bzw. schichtende | 25 mg/l | - Adopted Value) | 400 ppm |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name | available thes | n: expositionsend blut: expositions | Shor below. de, bzv sende, at end | rt time value (TLV - Ado w. schichtende , bzw. schichtende of workweek Fest | 25 mg/l 25 mg/l 40 mg/L Number | | 400 ppm |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name sopropanol (Volatile Organic con | available thes | n: expositionsend blut: expositions | Shor pelow. de, bzv sende, at end | rt time value (TLV - Ado w. schichtende , bzw. schichtende of workweek Fest NIOSH | 25 mg/l 25 mg/l 40 mg/L Number 2549 | | 400 ppm |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name sopropanol (Volatile Organic con sopropyl Alcohol (Alcohols I) | available thes | n: expositionsend blut: expositions | Shor pelow. de, bzv sende, at end o | rt time value (TLV - Ado w. schichtende , bzw. schichtende of workweek Fest NIOSH NIOSH | 25 mg/l 25 mg/l 40 mg/L Number 2549 1400 | | 400 ppm |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name sopropanol (Volatile Organic con sopropyl Alcohol (Alcohols I) sopropyl Alcohol | available thes | n: expositionsend blut: expositions | Shor pelow. de, bzv sende, at end d | rt time value (TLV - Add w. schichtende , bzw. schichtende of workweek Fest NIOSH NIOSH NIOSH | 25 mg/l 25 mg/l 40 mg/L Number 2549 1400 3900 | | 400 ppm |
| 2-propanol b) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name sopropanol (Volatile Organic con sopropyl Alcohol (Alcohols I) sopropyl Alcohol sopropyl Alcohol | available thes | n: expositionsend blut: expositions ne: end of shift a | Shor below. de, bzy sende, at end o | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek Fest NIOSH NIOSH NIOSH NIOSH | 25 mg/l 25 mg/l 40 mg/L Number 2549 1400 | | 400 ppm |
| 2-propanol 2) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name sopropanol (Volatile Organic con sopropyl Alcohol (Alcohols I) sopropyl Alcohol sopropyl Alcohol Sopropyl Alcohol B Applicable limit values when u f limit values are applicable 4 Threshold values | available thes | n: expositionsend Iblut: expositions ne: end of shift a ne: end of shift a stance or mixture | Shor below. de, bzy sende, at end o | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek Fest NIOSH NIOSH NIOSH NIOSH DSHA DSHA ntended | 25 mg/l 25 mg/l 40 mg/L Number 2549 1400 3900 | | 400 ppm |
| 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propan-2-ol (Aceton) 2-propan-2-ol (Aceton) 2-propanol (Acetone) 2-Propanol (Acetone) 2-Propanol (Acetone) 2-Propanol (Volatile Organic con sopropyl Alcohol (Alcohols I) sopropyl Alcohol 3-Applicable limit values when u f limit values are applicable 3-Threshold values 2-Protect - Workers | available thes | n: expositionsend iblut: expositions ne: end of shift a e: end of shift a stance or mixtur e these will be | Shor below. de, bzv sende, at end d h t re as in set est est set est est est set est est est est set est est est est est set est est est est est est set est est est est est est est set est est est est est est est est est | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek Fest NIOSH NIOSH NIOSH NIOSH DSHA DSHA ntended | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 | Background, Nonsp | 400 ppm |
| 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol (Aceton) 2-propanol (Acetone) 2-propanol (Acetone) 2-propanol (Volatile Organic con 2-propyl Alcohol 2-propyl Alcohol 2-propyl Alcohol 3-propyl A | available thes Urin Voll Urin using the subs and availabl isoalkanes, cy | n: expositionsend Iblut: expositions ne: end of shift a stance or mixtur e these will be <u>cclics, < 5% n-hex</u> | Shor below. de, bzv sende, at end d h t f f f f f f f f f f f f f f f f f f | rt time value (TLV - Add w. schichtende , bzw. schichtende of workweek Test NIOSH NIOSH NIOSH NIOSH DSHA tended d below. | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 | | 400 ppm |
| 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propan-2-ol (Aceton) 2-propan-2-ol (Aceton) 2-propanol (Acetone) 2-Propanol (Acetone) 2-Propanol (Acetone) 2-Propanol (Volatile Organic con sopropyl Alcohol (Alcohols I) sopropyl Alcohol 3-Applicable limit values when u f limit values are applicable 3-Threshold values 2-Protect - Workers | available thes Urin Voll using the subs and availabl isoalkanes, cy Type Long-te | n: expositionsend blut: expositions ne: end of shift a stance or mixture e these will be <u>cclics, < 5% n-hex</u> erm systemic ef | Shor Delow. de, bzv sende, sende, at end of re as in re as in the lister xane ffects | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek Test NIOSH NIOSH NIOSH OSHA DSHA tended d below. | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 | Background, Nonsp | 400 ppm |
| 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propan-2-ol (Aceton) 2-propan-2-ol (Aceton) 2-Propanol (Acetone) 2-Propanol (Acetone) 2-Propanol (Acetone) 2-Sampling methods 2-product name 3-product name 3-propyl Alcohol (Alcohols I) 3-propyl Alcohol 3-propy | available thes Urin Voll using the subs and availabl isoalkanes, cy Type Long-te | n: expositionsend Iblut: expositions ne: end of shift a stance or mixtur e these will be <u>cclics, < 5% n-hex</u> | Shor Delow. de, bzv sende, sende, at end of re as in re as in the lister xane ffects | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek Test NIOSH NIOSH NIOSH OSHA DSHA tended d below. | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 | Background, Nonsp | 400 ppm |
| 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propan-2-ol (Aceton) 2-propan-2-ol (Aceton) 2-Propanol (Acetone) 2-Propanol (Acetone) 2-Propanol (Acetone) 2-Sampling methods 2-product name 3-product name 3-propyl Alcohol (Alcohols I) 3-propyl Alcohol 3-propy | available thes Urin Voll using the subs and availabl isoalkanes, cy Type Long-te | n: expositionsend blut: expositions ne: end of shift a stance or mixture e these will be <u>cclics, < 5% n-hex</u> erm systemic ef | Shor Delow. de, bzv sende, sende, at end of re as in re as in the lister xane ffects | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek Test NIOSH NIOSH NIOSH OSHA DSHA tended d below. | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 | Background, Nonsp | 400 ppm |
| 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propanol 2-propan-2-ol (Aceton) 2-propan-2-ol (Aceton) 2-Propanol (Acetone) 2-Propanol (Acetone) 2-Propanol (Acetone) 2-Sampling methods 2-product name 3-product name 3-product name 3-propyl Alcohol (Alcohols I) 3-propyl Alcohol 3-propyl | available thes Urin Voll Urin using the subs and availabl isoalkanes, cy Type Long-te Long-te Long-te | n: expositionsend blut: expositions ne: end of shift a stance or mixture e these will be rclics, < 5% n-hex erm systemic ef erm systemic ef | Shor below. de, bzz sende, sende, at end o n n n n n n n n n n n n n n n n n n n | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek rest NIOSH NIOSH NIOSH OSHA d below. inhalation dermal inhalation | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 Value 2035 mg/m ³ 773 mg/kg bw/ | Background, Nonsp | 400 ppm |
| 2-propanol 2) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name sopropanol (Volatile Organic con sopropyl Alcohol (Alcohols I) sopropyl Alcohol 3 Applicable limit values when u f limit values are applicable 3 Threshold values 2 NEL/DMEL - Workers 2 NCL/DMEL - Workers 2 NCL/DMEL - UNEL/DMEL) DNEL 2 Tropan-2-ol Effect level (DNEL/DMEL) DNEL | available thes Urin Voll using the subs and availabl isoalkanes, Cy Long-te Long-te Long-te Long-te | n: expositionsend blut: expositions ne: end of shift a stance or mixture e these will be <u>cclics, < 5% n-hex</u> erm systemic ef | Shor below. de, bzz sende, sende, at end o n n n n n n n n n n n n n n n n n n n | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek rest NIOSH NIOSH NIOSH OSHA d below. inhalation dermal inhalation | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 Value 2035 mg/m ³ 773 mg/kg bw/ | Background, Nonsp | 400 ppm |
| Propanol National biological limit value Ilimit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) Sampling methods roduct name sopropanol (Acetone) Sampling methods roduct name sopropyl Alcohol (Alcohols I) sopropyl Alcohol Applicable limit values when u f limit values are applicable Threshold values DNEL/DMEL - Workers vydrocarbons, C6-C7, n-alkanes, Effect level (DNEL/DMEL) DNEL DNEL DNEL | available thes Urin Voll using the subs and availabl isoalkanes, Cy Type Long-te Long-te Long-te | n: expositionsend blut: expositionsend ne: end of shift ar et end of shift ar stance or mixtur e these will be rclics, < 5% n-hex erm systemic ef erm systemic ef erm systemic ef | Shor Delow. de, bzv sende, sende, at end of re as in ffects ffects ffects ffects | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek rest NIOSH NIOSH NIOSH OSHA d below. inhalation dermal inhalation | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 Value 2035 mg/m ³ 773 mg/kg bw/ | Background, Nonsp | 400 ppm |
| Propanol National biological limit value Ilimit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) Sampling methods roduct name sopropanol (Acetone) Sampling methods roduct name sopropyl Alcohol (Alcohols I) sopropyl Alcohol Applicable limit values when u f limit values are applicable Threshold values DNEL/DMEL - Workers vydrocarbons, C6-C7, n-alkanes, Effect level (DNEL/DMEL) DNEL DNEL DNEL | available thes Urin Voll using the subs and availabl isoalkanes, Cy Type Long-te Long-te Long-te | n: expositionsend blut: expositionsend ne: end of shift ar et end of shift ar stance or mixtur e these will be rclics, < 5% n-hex erm systemic ef erm systemic ef erm systemic ef | Shor Delow. de, bzv sende, sende, at end of re as in ffects ffects ffects ffects | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek rest NIOSH NIOSH NIOSH OSHA d below. inhalation dermal inhalation | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 Value 2035 mg/m ³ 773 mg/kg bw/ | Background, Nonsp | 400 ppm |
| 2-propanol 2) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name sopropanol (Volatile Organic con sopropyl Alcohol (Alcohols I) sopropyl Alcohol 3 Applicable limit values when u f limit values are applicable 3 Threshold values DNEL/DMEL - Workers Soverations, C6-C7, n-alkanes, Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL DNEL DNEL DNEL DNEL | available thes Urin Voll using the subs and availabl isoalkanes, Cy Type Long-te Long-te Long-te Long-te Long-te Type | n: expositionsend blut: expositionsend ne: end of shift ar et end of shift ar stance or mixtur e these will be rclics, < 5% n-hex erm systemic ef erm systemic ef erm systemic ef | Shor pelow. de, bzz sende, sende, at end of tend of | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek Test NIOSH NIOSH NIOSH OSHA tended d below. inhalation dermal | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 Value 2035 mg/m ³ 773 mg/kg bw/ Value 500 mg/m ³ 888 mg/kg bw/ | Background, Nonsp | 400 ppm |
| 2-propanol 2) National biological limit value f limit values are applicable and Germany Propan-2-ol (Aceton) Propan-2-ol (Aceton) USA (BEI-ACGIH) 2-Propanol (Acetone) 2 Sampling methods Product name sopropanol (Volatile Organic color sopropyl Alcohol (Alcohols I) sopropyl Alcohol 3 Applicable limit values when u f limit values are applicable 3 Threshold values DNEL/DMEL - Workers Sydrocarbons, C6-C7, n-alkanes, Effect level (DNEL/DMEL) DNEL DNEL DNEL DNEL Effect level (DNEL/DMEL) Effect level (DNEL/DM | available thes Urin Voll using the subs and availabl isoalkanes, CV Type Long-te Long-te Long-te Long-te Long-te Long-te | n: expositionsend blut: expositions ne: end of shift ar ne: end of shift ar stance or mixtur e these will be rclics, < 5% n-hex erm systemic efferm systemic e | Shor pelow. de, bzz sende, sende, at end of at end of re as in re as in re as in ffects ffects ffects ffects ffects ffects | rt time value (TLV - Add w. schichtende bzw. schichtende of workweek Test NIOSH NIOSH NIOSH OSHA d below. inhalation dermal inhalation dermal | 25 mg/l 25 mg/l 25 mg/l 40 mg/L 2549 1400 3900 5001 5001 Value 2035 mg/m ³ 773 mg/kg bw/ Value 500 mg/m ³ 888 mg/kg bw/ | Background, Nonsp | 400 ppm |

| propan-2-ol | | | | | | | |
|--------------------------|---------------------------------------|------------------|--------|--|--|--|--|
| Effect level (DNEL/DMEL) | Туре | Value | Remark | | | | |
| DNEL | Long-term systemic effects inhalation | 89 mg/m³ | | | | | |
| | Long-term systemic effects dermal | 319 mg/kg bw/day | | | | | |
| | Long-term systemic effects oral | 26 mg/kg bw/day | | | | | |

8.1.5 Control banding

If applicable and available it will be listed below.

8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly.

8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Avoid prolonged and repeated contact with skin. Do not eat, drink or smoke during work.

a) Respiratory protection:

Full face mask with filter type A at conc. in air > exposure limit.

b) Hand protection:

Protective gloves against chemicals (EN 374).

| Materials | Remark |
|-----------------------------------|----------------------|
| neoprene (chloroprene rubber) | Excellent resistance |
| nitrile rubber | Excellent resistance |
| nitrile rubber/PVC | Excellent resistance |
| polyethylene/ethylenevinylalcohol | Excellent resistance |
| PVC | Good resistance |
| natural rubber | Poor resistance |

c) Eye protection:

Protective goggles (EN 166).

d) Skin protection:

Protective clothing (EN 14605 or EN 13034). Head/neck protection.

8.2.3 Environmental exposure controls:

See sections 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical form | Aerosol |
|---------------------------|-------------------------------------|
| Odour | No data available on odour |
| Odour threshold | No data available in the literature |
| Colour | Colourless |
| Particle size | Not applicable (aerosol) |
| Explosion limits | No data available in the literature |
| Flammability | Extremely flammable aerosol. |
| Log Kow | Not applicable (mixture) |
| Dynamic viscosity | Not applicable (aerosol) |
| Kinematic viscosity | > 20.5 mm²/s ; 40 °C ; Liquid |
| Melting point | Not applicable |
| Boiling point | No data available in the literature |
| Relative vapour density | No data available in the literature |
| Vapour pressure | No data available in the literature |
| Solubility | Water ; insoluble |
| Relative density | No data available in the literature |
| Absolute density | No data available in the literature |
| Decomposition temperature | No data available in the literature |
| Auto-ignition temperature | Not applicable |
| Flash point | < 23 °C ; Liquid |
| рН | Not applicable (aerosol) |

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

10.2. Chemical stability

Unstable on exposure to heat.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Precautionary measures

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5. Incompatible materials

No data available.

10.6. Hazardous decomposition products

Upon combustion: CO and CO2 are formed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 Test results

Acute toxicity

Cleaner C-20

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Route of exposure | Parameter | Method | Value | Exposure time | Species | Value | Remark |
|----------------------|-----------|--------|----------------------------------|---------------|------------------------|--------------------|--------|
| | | | | | | determination | |
| Oral | LD50 | | > 5840 mg/kg bw | | Rat | Read-across | |
| Dermal | LD50 | | 2800 mg/kg bw - 3100 mg/kg bw | | Rat (male / female) | Read-across | |
| Inhalation (vapours) | LC50 | | > 25.2 mg/l | | Rat (male / female) | Experimental value | |

propan-2-ol

| Route of exposure | Parameter | Method | Value | Exposure time | Species | Value | Remark |
|----------------------|-----------|---------------------------|----------------|---------------|------------------------|--------------------|--------|
| | | | | | | determination | |
| Oral | LD50 | Equivalent to OECD 401 | 5840 mg/kg bw | | Rat | Experimental value | |
| Dermal | LD50 | Equivalent to OECD 402 | 16400 ml/kg bw | 24 h | Rabbit | Experimental value | |
| Inhalation (vapours) | LC50 | Equivalent to OECD 403 | > 10000 ppm | - | Rat (male / female) | Experimental value | |

Conclusion

Not classified for acute toxicity

Corrosion/irritation

Cleaner C-20

No (test)data on the mixture available

Classification is based on the relevant ingredients hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Route of exposure | Result | Method | Exposure time | Time point | Species | Value determination | Remark |
|-------------------|----------------|---------------------------|---------------|-------------------------------|---------|------------------------|-------------------------------------|
| Eye | Not irritating | Equivalent to OECD 405 | | 24; 48; 72 hours | Rabbit | Read-across | Single treatmen |
| Skin | Irritating | Equivalent to OECD 404 | 4 h | 24; 48; 72 hours | Rabbit | Experimental value | |
| opan-2-ol | • | | | | | • | |
| Route of exposure | Result | Method | Exposure time | Time point | Species | Value determination | Remark |
| Eye | Irritating | Equivalent to OECD 405 | | 1; 2; 3; 4; 7; 10; 14 days | Rabbit | Experimental value | Single treatment without rinsing |
| Skin | Not irritating | | 4 h | 4; 24; 48; 72 hours | Rabbit | Experimental value | |

Conclusion

Causes skin irritation. Causes serious eye irritation.

Not classified as irritating to the respiratory system

Respiratory or skin sensitisation

Cleaner C-20

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Route of exposure | Result | Method | Exposure time | Observation time | Species | Value determination | Remark |
|-------------------|-----------------|--------------------|---------------|------------------|------------------|---------------------|--------|
| | | | | point | | | |
| Skin | Not sensitizing | Equivalent to OECD | | 24; 48 hours | Guinea pig (male | Read-across | |
| | | 406 | | | / female) | | |

propan-2-ol

| Route of exposure | Result | Method | Observation time point | Species | Value determination | Remark |
|-------------------|-----------------|----------|-------------------------------|-------------------------------|---------------------|--------|
| Dermal | Not sensitizing | OECD 406 | | Guinea pig (male / female) | Experimental value | |

Conclusion

Not classified as sensitizing for inhalation

Not classified as sensitizing for skin

Specific target organ toxicity

Cleaner C-20

No (test)data on the mixture available

Classification is based on the relevant ingredients

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Route of exposure | Parameter | Method | Value | Organ | Effect | Exposure time | | Value determination |
|-------------------------|-----------|---------------------------|--------------------------------|-------|-----------------------------------|--|------------------------|------------------------|
| Dermal | NOAEL | Equivalent to OECD 453 | 0.5 ml | | | 52 weeks (3 times / week) - 104 weeks (3 times / week) | · · · | Experimental value |
| Inhalation (vapours) | NOAEC | Subacute toxicity test | 14000 mg/m ³ air | | No adverse systemic effects | 3 days (8h / day) | Rat (male) | Experimental value |
| Inhalation (vapours) | NOAEC | Equivalent to OECD 413 | 8117 mg/m³ air | Liver | No effect | 13 weeks (6h / day, 5 days / week) | Rat (male / female) | Read-across |
| Inhalation | | | STOT SE cat.3 | | | | | Literature study |

propan-2-ol

| Route of exposure | Parameter | Method | Value | Organ | Effect | Exposure time | · · · · · · | Value determination |
|-------------------------|-----------|---------------------------|----------|------------------------------|--------------------------|--|-------------|------------------------|
| Oral | | | | | | | | Data waiving |
| Dermal | | | | | | | | Data waiving |
| Inhalation (vapours) | NOAEC | OECD 451 | 5000 ppm | | | 104 weeks (6h / day, 5 days / week) | · · · | Experimental value |
| Inhalation (vapours) | | Equivalent to OECD 403 | 5000 ppm | Central nervous system | Drowsiness, dizziness | 6 h | · · · | Experimental value |

Conclusion

May cause drowsiness or dizziness.

Not classified for subchronic toxicity

Mutagenicity (in vitro)

Cleaner C-20

No (test)data on the mixture available

Judgement is based on the relevant ingredients

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Result | Method | Test substrate | Effect | Value determination | Remark |
|--|------------------------|--|-----------|---------------------|--------|
| Negative with metabolic activation, negative without metabolic activation | Equivalent to OECD 471 | Bacteria (S. typhimurium and E. coli) | No effect | Read-across | |
| Negative | Equivalent to OECD 473 | Rat liver cells | No effect | Read-across | |

| propan-2-ol | | | | | |
|--|------------------------|--------------------------------|-----------|---------------------|--------|
| Result | Method | Test substrate | Effect | Value determination | Remark |
| Negative with metabolic activation, negative without metabolic activation | Equivalent to OECD 471 | Bacteria (S.typhimurium) | No effect | Experimental value | |
| Negative with metabolic activation, negative without metabolic activation | Equivalent to OECD 476 | Chinese hamster ovary (CHO) | No effect | Experimental value | |

Mutagenicity (in vivo)

Cleaner C-20

No (test)data on the mixture available

Judgement is based on the relevant ingredients

propan-2-ol

| Result | Method | Exposure time | Test substrate | Organ | Value determination |
|----------------------------|--------------------|---------------|-----------------------|-------|---------------------|
| Negative (Intraperitoneal) | Equivalent to OECD | | Mouse (male / female) | | Experimental value |
| | 474 | | | | |

Conclusion

Not classified for mutagenic or genotoxic toxicity

Carcinogenicity

Cleaner C-20

No (test)data on the mixture available

Judgement is based on the relevant ingredients

| pro | pan-2-ol |
|-----|----------|
| | |

| Route of | Parameter | Method | Value | Exposure time | Species | Effect | Organ | Value determination |
|------------|-----------|----------|----------|----------------------|-------------|-----------------|-------|---------------------|
| exposure | | | | | | | | |
| Inhalation | NOEL | OECD 451 | 5000 ppm | 104 weeks (6h / day, | Rat (male / | No carcinogenic | | Experimental value |
| (vapours) | | | | 5 days / week) | female) | effect | | |

Conclusion

Not classified for carcinogenicity

Reproductive toxicity

Cleaner C-20

No (test)data on the mixture available

Judgement is based on the relevant ingredients hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| | Parameter | Method | Value | Exposure time | Species | Effect | Organ | Value determination |
|------------------------|-----------|---------------------------|--------------------|--|------------------------|-----------|-------|------------------------|
| Developmental toxicity | NOAEL | Equivalent to OECD 414 | 10560 mg/m³ air | 10 days (6h / day) | Mouse | No effect | | Read-across |
| Maternal toxicity | NOAEL | Equivalent to OECD 414 | 3168 mg/m³ air | 10 days (6h / day) | Mouse (female) | No effect | | Read-across |
| Effects on fertility | NOAEL | Equivalent to OECD 416 | 31680 mg/m³ air | 13 weeks (6h / day, 5 days / week) | Rat (male / female) | No effect | | Read-across |

propan-2-ol

| | Parameter | Method | Value | Exposure time | Species | Effect | - 0. | Value determination |
|---|-----------|---------------------------|---------------------|---------------|------------------------|-----------|------|------------------------|
| Developmental toxicity (Oral (stomach tube)) | NOAEL | Equivalent to OECD 414 | 400 mg/kg bw/day | 10 day(s) | Rat | No effect | | Experimental value |
| Maternal toxicity (Oral (stomach tube)) | NOAEL | Equivalent to OECD 414 | 400 mg/kg bw/day | 10 day(s) | Rat | No effect | | Experimental value |
| Effects on fertility (Oral (drinking water)) | NOAEL | Equivalent to OECD 415 | 853 mg/kg bw/day | | Rat (male / female) | No effect | | Experimental value |

Conclusion

Not classified for reprotoxic or developmental toxicity

Aspiration hazard

Judgement is based on high viscosity of the mixture Not classified for aspiration toxicity

Toxicity other effects

Cleaner C-20

No (test)data on the mixture available

Chronic effects from short and long-term exposure

Cleaner C-20

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Oil acne.

11.2. Information on other hazards

No evidence of endocrine disrupting properties

SECTION 12: Ecological information

12.1. Toxicity

Cleaner C-20

No (test)data on the mixture available

Classification is based on the relevant ingredients hydrocarbons, C6-C7, n-alkanes. isoalkanes. cvclics. < 5% n-hexane

| | Parameter | Method | Value | Duration | Species | Test design | Fresh/salt water | Value determination |
|---|-----------|----------|-----------------------|-----------|---------------------------|-----------------------|---------------------|------------------------------|
| Acute toxicity fishes | LL50 | OECD 203 | 11.4 mg/l | 96 h | Oncorhynchus mykiss | Semi-static system | Fresh water | Experimental value; GLP |
| Acute toxicity crustacea | EL50 | OECD 202 | 3 mg/l | 48 h | Daphnia magna | Static system | Fresh water | Experimental value; GLP |
| Toxicity algae and other aquatic plants | ErC50 | OECD 201 | 30 mg/l - 100 mg/l | 72 h | | Static system | Fresh water | Experimental value; GLP |
| Long-term toxicity fish | NOELR | | 2.045 mg/l | 28 day(s) | Oncorhynchus mykiss | | Fresh water | QSAR |
| Toxicity aquatic micro- organisms | EL50 | | 35.57 mg/l | 48 h | Tetrahymena pyriformis | | Fresh water | QSAR; Continuous exposure |

| | Parameter | Method | Value | Duration | Species | Test design | Fresh/salt water | Value determination |
|---|-----------------------|-------------------------------|---------------------------|------------|----------------------------|----------------------------|---------------------|---|
| Acute toxicity fishes | LC50 | Equivalent to OECD 203 | 9640 mg/l - 10000 mg/l | 96 h | Pimephales promelas | Flow- through system | Fresh water | Experimental value; Lethal |
| Acute toxicity crustacea | LC50 | Equivalent to OECD 202 | > 10000 mg/l | 24 h | Daphnia magna | Static system | Fresh water | Experimental value; Locomotor effect |
| Toxicity algae and other aquatic plants | Toxicity threshold | | 1800 mg/l | 7 day(s) | Scenedesmus quadricauda | Static system | Fresh water | Experimental value; Toxicity test |
| Long-term toxicity fish | NOELR | Petrotox computer model | > 1000 mg/l | 28 day(s) | Brachydanio rerio | | | Estimated value |
| Long-term toxicity aquatic crustacea | NOEC | | 141 mg/l | 16 day(s) | Daphnia magna | | Fresh water | Experimental value; Growth |
| Toxicity aquatic micro- organisms | Toxicity threshold | Equivalent to DIN 38412/8 | 1050 mg/l | 16 h | Pseudomonas putida | Static system | Fresh water | Experimental value; Toxicity test |
| | EC50 | ISO 8192 | 41676 mg/l | 30 minutes | Activated sludge | | | Experimental value |

Conclusion

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

| Biodegradation water | |
|----------------------|--|
|----------------------|--|

| | Method | Value | Duration | Value determination |
|-----|-----------|--------------------------|-----------|---------------------|
| | OECD 301F | 98 %; Oxygen consumption | 28 day(s) | Experimental value |
| pro | pan-2-ol | | - | |

Biodegradation water

| _ | | | | | | |
|---|------------------------------------|--------------------------|------------------------|---------------------|--|--|
| | Method | Value | Duration | Value determination | | |
| | EU Method C.5 | 53 %; Oxygen consumption | 5 day(s) | Experimental value | | |
| P | Phototransformation air (DT50 air) | | | | | |
| | Method | Value | Conc. OH-radicals | Value determination | | |
| | AOPWIN v1.92 | 17.668 h | 1.5E6 /cm ³ | Calculated value | | |

Conclusion

Water

Contains readily biodegradable component(s)

12.3. Bioaccumulative potential

Cleaner C-20 Log Kow

| Method | | | Cleane | r C-20 | | |
|---|--|--|---|--|---|--|
| | Remark | | Value | Te | emperature | Value determination |
| | Not appli | cable (mixture) | | | | |
| hydrocarbons, C6- | C7, n-alkanes, isoalkan | es, cyclics, < 5% n-ł | lexane | | | |
| Log Kow | <u>, , , , , , , , , , , , , , , , , , , </u> | | | | | |
| Method | Rema | rk | Value | | Temperature | Value determination |
| | | ta available | | | | |
| propan-2-ol | · · · · · | | • | | • | • |
| BCF fishes | | | | | | |
| Parameter | Method | Value | Duration | Species | 1 | Value determination |
| BCF | BCFBAF v3.01 | 1015 | | | | Estimated value |
| Log Kow | | | | | | |
| Method | Rema | rk | Value | | Temperature | Value determination |
| onclusion | | | 0.05 | | 25 °C | Weight of evidence approach |
| (log) Koc Parameter log Koc | | | Method SRC PCKOC | WIN v2 0 | Value 0.185 - 0.541 | Value determination |
| IOg KOC | | | SRC PCKOL | .00110 02.0 | 0.185 - 0.541 | |
| zone-depleting pot | | d in the list of fluori | nated greenhouse g | (5 | | |
| ot classified as da propan-2-ol roundwater | | one layer (Regulat | ion (EC) No 1005/2 | | n (EU) No 517/2014) | |
| <u>propan-2-ol</u> roundwater roundwater pollu | itant | 7 . 2 | | | n (EU) No 517/2014) | |
| <u>propan-2-ol</u> roundwater roundwater pollu TION 13: Di he information in | sposal consid | derations heral description. | ion (EC) No 1005/2 | 009) | | ched in annex. Always use the |
| propan-2-ol roundwater roundwater pollu TION 13: Di he information in elevant exposure | tant sposal consider this section is a ger | derations heral description. | ion (EC) No 1005/2 | 009) | | ched in annex. Always use the |
| propan-2-ol roundwater roundwater pollu TION 13: Di he information in elevant exposure 3.1. Waste trea | tant Sposal consi this section is a ger scenarios that corre | derations heral description. | ion (EC) No 1005/2 | 009) | | ched in annex. Always use the |
| propan-2-ol roundwater roundwater pollu TION 13: Di he information in elevant exposure 3.1. Waste trea 13.1.1 Provisions European Unio Hazardous | tant Sposal Consid this section is a ger scenarios that corre stment methods s relating to waste n | derations beral description ispond to your ide Directive 2008/93 | ion (EC) No 1005/2 If applicable and a entified use. B/EC, as amended | 009) vailable, expo | osure scenarios are attac | ched in annex. Always use the Regulation (EU) No 2017/997. |
| propan-2-ol roundwater roundwater pollu TION 13: Di he information in elevant exposure 3.1. Waste treat 13.1.1 Provisions European Unio Hazardous Waste ma 16 05 04* substance | s relating to waste waste according to terial code (Directiv (gases in pressure c s). Depending on bra | derations leral description lespond to your ide Directive 2008/98 e 2008/98/EC, Dec ontainers and dis | ion (EC) No 1005/2 If applicable and a entified use. B/EC, as amended cision 2000/0532/ carded chemicals | 009) vailable, expo by Regulation EC). : gases in pres | osure scenarios are attac (EU) No 1357/2014 and l | Regulation (EU) No 2017/997. ng halons) containing hazardou |
| propan-2-ol roundwater roundwater pollu TION 13: Di he information in elevant exposure 3.1. Waste trea 13.1.1 Provisions European Unio Hazardous Waste ma 16 05 04* substance 13.1.2 Disposal m Remove w Different t manageme shall take | tant sposal consider this section is a ger scenarios that correct the ment methods s relating to waste n s waste according to terial code (Directiv (gases in pressure construction) s). Depending on bra- nethods aste in accordance ypes of hazardous vent of the waste. Ha | Directive 2008/98 e 2008/98/EC, Decontainers and dis anch of industry a with local and/or vaste shall not be zardous waste sh ures to prevent ri | ion (EC) No 1005/2 If applicable and a entified use. B/EC, as amended cision 2000/0532/ carded chemicals nd production pro national regulatio mixed together if all be managed re sks of pollution on | vailable, expo by Regulation EC). gases in pres cess, also oth ns. Hazardous this may enta sponsibly. All | csure scenarios are attac (EU) No 1357/2014 and l ssure containers (includi er waste codes may be a waste shall not be mixe il a risk of pollution or cr entities that store, trans | Regulation (EU) No 2017/997. ng halons) containing hazardou |

SECTION 14: Transport information

Road (ADR)

| .1. UN number | | | | |
|-------------------------------|---------|--|--|--|
| UN number 1950 | | | | |
| 14.2. UN proper shipping name | | | | |
| aerosols | | | | |
| - | · · · · | | | |

Revision number: 0000

| 11/15 |
|-------|
|-------|

Publication date: 2023-06-29

BIG number: 69170

| C | leaner C-20 |
|---|---|
| 14.3. Transport hazard class(es) | |
| Hazard identification number | |
| Class | 2 |
| Classification code | 5F |
| | 5F |
| L4.4. Packing group | |
| Packing group | |
| Labels | 2.1 |
| I4.5. Environmental hazards | |
| Environmentally hazardous substance mark | yes |
| 14.6. Special precautions for user | |
| Special provisions | 190 |
| Special provisions | 327 |
| Special provisions | 344 |
| Special provisions | 625 |
| | |
| Limited quantities | Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) |
| (RID) | |
| L4.1. UN number | |
| UN number | 1950 |
| L4.2. UN proper shipping name | 1 |
| Proper shipping name | aerosols |
| | aci 03013 |
| L4.3. Transport hazard class(es) | |
| Hazard identification number | 23 |
| Class | 2 |
| Classification code | 5F |
| L4.4. Packing group | |
| Packing group | |
| Labels | 2.1 |
| L4.5. Environmental hazards | £.1 |
| Environmentally hazardous substance mark | Voc |
| | yes |
| L4.6. Special precautions for user | |
| Special provisions | 190 |
| Special provisions | 327 |
| Special provisions | 344 |
| Special provisions | 625 |
| Limited quantities | Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass) |
| ind waterways (ADN) | |
| I4. <u>1. UN number/ID number</u> | |
| UN number/ID number | 1950 |
| L4.2. UN proper shipping name | |
| Proper shipping name | aerosols |
| | |
| 4.3. Transport hazard class(es) | - |
| Class | 2 |
| Classification code | |
| | 5F |
| | 5F |
| | 5F |
| 4.4. Packing group Packing group | |
| 4.4. Packing group Packing group Labels | 2.1 |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards | 2.1 |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark | |
| 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user | 2.1 yes |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions | 2.1 yes 190 |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user | 2.1 yes |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions | 2.1 yes 190 |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions | 2.1 yes 190 327 344 |
| 4.4. Packing group Packing group Labels .4.5. Environmental hazards Environmentally hazardous substance mark .4.6. Special precautions for user Special provisions | 2.1 yes 190 327 344 625 |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions | 2.1 yes 190 327 344 625 |
| 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions Special provisions Special provisions Limited quantities | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging f |
| 4.4. Packing group Packing group Labels Labels Environmental hazards Environmentally hazardous substance mark Special precautions for user Special provisions Special provisions Special provisions Special provisions Limited quantities (IMDG/IMSBC) 4.1. UN number | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging fr liquids. A package shall not weigh more than 30 kg. (gross mass) |
| 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions Special provisions Limited quantities | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging f |
| 4.4. Packing group Packing group Labels Labels Environmental hazards Environmentally hazardous substance mark Special precautions for user Special provisions Special provisions Special provisions Limited quantities (IMDG/IMSBC) 4.1. UN number UN number | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging fr liquids. A package shall not weigh more than 30 kg. (gross mass) |
| 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions Special provisions Special provisions Limited quantities (IMDG/IMSBC) 4.1. UN number UN number 4.2. UN proper shipping name | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging fr liquids. A package shall not weigh more than 30 kg. (gross mass) 1950 |
| 4.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions Limited quantities (IMDG/IMSBC) 14.1. UN number UN number 14.2. UN proper shipping name Proper shipping name | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging fr liquids. A package shall not weigh more than 30 kg. (gross mass) |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Imited quantities IMDG/IMSBC 14.1. UN number UN number 14.2. UN proper shipping name Proper shipping name Proper shipping name 14.3. Transport hazard class(es) | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass) 1950 aerosols |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.5. Special precautions for user Special provisions Limited quantities (IMDG/IMSBC) 14.1. UN number UN number 14.2. UN proper shipping name Proper shipping name 14.3. Transport hazard class(es) Class | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging fr liquids. A package shall not weigh more than 30 kg. (gross mass) 1950 |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions Limited quantities (IMDG/IMSBC) 14.1. UN number UN number 14.2. UN proper shipping name Proper shipping name 14.3. Transport hazard class(es) Class 14.4. Packing group | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging fo liquids. A package shall not weigh more than 30 kg. (gross mass) 1950 aerosols |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.5. Special precautions for user Special provisions Limited quantities (IMDG/IMSBC) 14.1. UN number UN number 14.2. UN proper shipping name Proper shipping name 14.3. Transport hazard class(es) Class | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) 1950 2.1 2.1 |
| 14.4. Packing group Packing group Labels 14.5. Environmental hazards Environmentally hazardous substance mark 14.5. Environmental hazards Environmentally hazardous substance mark 14.6. Special precautions for user Special provisions Special provisions Special provisions Special provisions Limited quantities (IMDG/IMSBC) 14.1. UN number UN number 14.2. UN proper shipping name Proper shipping name 14.3. Transport hazard class(es) Class 14.4. Packing group | 2.1 yes 190 327 344 625 Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) 1950 aerosols |

| Cle | aner C-20 |
|--|--|
| Marine pollutant | Ρ |
| Environmentally hazardous substance mark | yes |
| 4.6. Special precautions for user | |
| Special provisions | 190 |
| Special provisions | 277 |
| Special provisions | 327 |
| Special provisions | 344 |
| Special provisions | 381 |
| Special provisions | 63 |
| Special provisions | 959 |
| Limited quantities | Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass) |
| 4.7. Maritime transport in bulk according to IMO instruments | |
| Annex II of MARPOL 73/78 | Not applicable |
| ICAO-TI/IATA-DGR) 4.1. UN number/ID number UN number/ID number | 1950 |
| | |
| 4.2. UN proper shipping name | |
| 4.2. UN proper shipping name Proper shipping name | aerosols, flammable |
| | |
| Proper shipping name | aerosols, flammable |
| Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group | |
| Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group | 2.1 |
| Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels | |
| Proper shipping name 1.3. Transport hazard class(es) Class 1.4. Packing group Packing group Labels 1.5. Environmental hazards | 2.1 |
| Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark | 2.1 |
| Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user | 2.1 2.1 yes |
| Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions | 2.1 2.1 yes A145 |
| Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions Special provisions | 2.1 2.1 yes A145 A167 |
| Proper shipping name 4.3. Transport hazard class(es) Class 4.4. Packing group Packing group Labels 4.5. Environmental hazards Environmentally hazardous substance mark 4.6. Special precautions for user Special provisions | 2.1 2.1 yes A145 |

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European legislation:

VOC content Directive 2010/75/EU

| VOC content | Remark |
|-------------|--------|
| 100 % | |

Directive 2012/18/EU (Seveso III)

| Threshold values under normal circumstances | | | | | |
|---|----------------------|----------------------|-------|---|--|
| Substance or category | Low tier (tonnes) | Top tier (tonnes) | Group | For this substance or mixture the summation rule has to be applied for: | |
| E2 Hazardous to the Aquatic Environment in Category Chronic 2 | 200 | 500 | None | Eco-toxicity | |
| P3b FLAMMABLE AEROSOLS | 5000 (net) | 50000 (net) | None | Flammability | |

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

| and use of certain dangerou | s substances, mixtures and articles. | |
|---|--|--|
| | Designation of the substance, of the group of | Conditions of restriction |
| | substances or of the mixture | |
| hydrocarbons, C6-C7, n-alkanes, | Liquid substances or mixtures fulfilling the | 1. Shall not be used in: |
| isoalkanes, cyclics, < 5% n-hexane | criteria for any of the following hazard classes | - ornamental articles intended to produce light or colour effects by means of different |
| propan-2-ol | or categories set out in Annex I to Regulation | phases, for example in ornamental lamps and ashtrays, |
| | (EC) No 1272/2008: | tricks and jokes, |
| | (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 | - games for one or more participants, or any article intended to be used as such, even with |
| | types A and B, 2.9, 2.10, 2.12, 2.13 categories | ornamental aspects, |
| | 1 and 2, 2.14 categories 1 and 2, 2.15 types A | Articles not complying with paragraph 1 shall not be placed on the market. |
| | to F; | 3. Shall not be placed on the market if they contain a colouring agent, unless required for |
| | (b) hazard classes 3.1 to 3.6, 3.7 adverse | fiscal reasons, or perfume, or both, if they: |
| | effects on sexual function and fertility or on | can be used as fuel in decorative oil lamps for supply to the general public, and, |
| | development, 3.8 effects other than narcotic | present an aspiration hazard and are labelled with H304, |
| | effects, 3.9 and 3.10; | 4. Decorative oil lamps for supply to the general public shall not be placed on the market |
| | (c) hazard class 4.1; | unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted |
| | (d) hazard class 5.1. | by the European Committee for Standardisation (CEN). |
| | | 5. Without prejudice to the implementation of other Community provisions relating to the |
| | | classification, packaging and labelling of dangerous substances and mixtures, suppliers shall |
| | | ensure, before the placing on the market, that the following requirements are met: |
| | | |
| | | |

| | Cleane | r C-20 |
|---|---|--|
| | | a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life- threatening lung damage"; b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010. |
| isoalkanes, cyclics, < 5% n-hexane | Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not. | Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: metallic glitter intended mainly for decoration, artificial snow and frost, "whoopee" cushions, silly string aerosols, imitation excrement, horns for parties, decorative flakes and foams, artificial cobwebs, stink bombs. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: "For professional users only". By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated. |
| | Substances falling within one or more of the following points: (a) substances classified as any of the following in Part 3 of Annex VI to Regulation (EC) No 1272/2008: — carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, or germ 2, but excluding any such substances classified due to effects only following exposure by inhalation — reproductive toxicant category 1A, 1B or 2 but excluding any such substances classified due to effects only following exposure by inhalation — skin sensitiser category 1, 1A or 1B — skin corrosive category 1, 1A or 1B — skin corrosive category 1 or eye tritant category 2 (b) substances listed in Annex II to Regulation (EC) No 1223/2009 of the European Parliament and of the Council (c) substances listed in Annex IV to Regulation (EC) No 1223/2009 for which a condition is specified in at least one of the columns g, h and i of the table in that Annex (J) substances listed in Appendix 13 to this Annex. The ancillary requirements in paragraphs 7 and 8 of column 2 of this entry apply to all mixtures for use for tattooing purposes, whether or not they contain a substance falling within points (a) to (d) of this column of this entry. | Mixtures for tattooing purposes are subject to the restrictions of Regulation (EU) 2020/2081 |
| <u>National legislation Belgium</u> <u>Cleaner C-20</u> No data available <u>propan-2-ol</u> Agents cancérigènes, mutagènes et reprotoxiques | alcool isopropylique; VI.2.2.; Liste des p l'acide fort dans la fabrication d'alcool is | rocédés au cours desquels une substance ou un mélange se dégage; Procédé à sopropylique. |
| (Code du bien-être au travail, Livre VI, titre 2) National legislation The Netherlands | | |
| Cleaner C-20 | - | < (ADAA) |
| Waterbezwaarlijkheid <u>National legislation France</u> <u>Cleaner C-20</u> No data available | A (2); Algemene Beoordelingsmethodiel | |
| | | Publication date: 2023-06-29 |
| evision number: 0000 | | BIG number: 69170 13 / 15 |

| hydrocarbons, C6-C7, n-alkan | s, isoalkanes, cyclics, < 5% n-hexane | |
|------------------------------|--|--|
| Catégorie cancérogène | Hydrocarbures en C6-C12 (ensemble des,vapeurs) | |
| Catégorie mutagène | Hydrocarbures en C6-C12 (ensemble des,vapeurs) | |

National legislation Germany

| <u>Cleaner C-20</u> | | | | |
|--|-----------------------|---|--|--|
| | Lagerklasse (TRGS510) | 2B: Aerosolpackungen und Feuerzeuge | | |
| | WGK | 2; Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen (AwSV) - 18. April 2017 | | |
| hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane | | | | |
| | TA-Luft | 5.2.5 | | |
| propan-2-ol | | | | |
| | TA-Luft | 5.2.5 | | |
| | TRGS900 - Risiko der | Propan-2-ol; Y; Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen | | |
| | Fruchtschädigung | Grenzwertes nicht befürchtet zu werden | | |

National legislation Austria

Cleaner C-20

No data available

National legislation United Kingdom

Cleaner C-20 No data available

Other relevant data Cleaner C-20

No data available

| p | ropan-2-ol | |
|---|-----------------------|----------------|
| | IARC - classification | 3; Isopropanol |
| | TLV - Carcinogen | 2-propanol; A4 |

15.2. Chemical safety assessment

No chemical safety assessment is required for a mixture.

SECTION 16: Other information

Full text of any H- and EUH-statements referred to under section 3:

- H222 Extremely flammable aerosol.
- H225 Highly flammable liquid and vapour.
- H229 Pressurised container: May burst if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

| (*) | INTERNAL CLASSIFICATION BY BIG |
|--------------|---|
| ADI | Acceptable daily intake |
| AOEL | Acceptable operator exposure level |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration Factor |
| BEI | Biological Exposure Indices |
| CLP (EU-GHS) | Classification, labelling and packaging (Globally Harmonised System in Europe) |
| DMEL | Derived Minimal Effect Level |
| DNEL | Derived No Effect Level |
| EC10 | Effect Concentration 10 % |
| EC50 | Effect Concentration 50 % |
| ErC50 | EC50 in terms of reduction of growth rate |
| GLP | Good Laboratory Practice |
| LC0 | Lethal Concentration 0 % |
| LC50 | Lethal Concentration 50 % |
| LD50 | Lethal Dose 50 % |
| LOAEC/LOAEL | Lowest Observed Adverse Effect Concentration/Lowest Observed Adverse Effect Level |
| NOAEC/NOAEL | No Observed Adverse Effect Concentration/No Observed Adverse Effect Level |
| NOEC/NOEL | No Observed Effect Concentration/No Observed Effect Level |
| OECD | Organisation for Economic Co-operation and Development |
| PBT | Persistent, Bioaccumulative & Toxic |
| PNEC | Predicted No Effect Concentration |
| STP | Sludge Treatment Process |
| vPvB | very Persistent & very Bioaccumulative |
| | |

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers

no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.